Vartest Laboratories

Quality Assurance & Compliance Testing
Utilizing Textile & Related Technologies
19 West 36th Street, 10th Floor
New York, NY 10018
Tel: 212 947 8391 Fax: 212 947 8719

www.vartest.com

ISO/IEC 17025 Certified Third Party Test Report

FILE: PIERRE.A061912A
SAMPLE IDENTIFIED BY CLIENT AS:
Fabric Submitted
Lot #: 1093456, 100% PolyTCS
Color Grey

CALIFORNIA TECHNICAL BULLETIN 117 SECTION E

LENGTH BURN TIME (sec)	BURN TYPE	WIDTH BURN TIME (sec)	BURN TYPE
SRU	DNI	SRU	DNI
SRU	DNI	SRU	DNI
SRU	DNI	SRU	DNI
SRU	DNI	SRU	DNI
SRU	DNI	SRU	DNI
Average: SRU seconds		**Average:** SRU seconds	

TEST RESULT : Passes

ABBREVIATIONS FOR BURN TYPE:

- **SFBB** - Surface flash base burn. Base starts burning at points other than the point of impingement.
- **DNI** - Does Not Ignite
- **BB** - Base burn.
- **IBE** - Ignited But Extinguished
- **SF** - Surface Flash
- **SFBBCF** - Surface flash base burn caused by surface flash

NOTE: SRU = Stop Cord Remains Unbroken - No Burn Time Available

VARTEST Tested & Evaluated LABORATORIES

ilac-MRA ACCREDITED Testing Cert #2180.01